Granville®

TECHNICAL DATA

Veedol
Powertron Plus 5W/40

1 Litre & 5 Litre

PRODUCT DESCRIPTION

Veedol Powertron Plus 5W-40 is an extremely modern, synthetic, universal motor oil based on specially selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:
high and very stable viscosity index; resistance against shearing; fast cold start; strong resistance against oxidation; safe lubrication film at very high temperatures; very good detergency and dispersion; strong protection against wear, corrosion and foaming.
Veedol Powertron Plus 5W-40 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	5016	5020618050162
5 Litre	5017	5020618050179

OEM APPROVALS

VW: 502.00 & 505.00
MB-Approval: 229.3

RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A3/B4
API: SN/CF
BMW: LL-01
Fiat: 9.55535-M2
GM: LL-B-025
Porsche: A40
PSA: B71 2296
Renault: RN0700 & RN0710
MB: 226.5

PRODUCT BENEFITS

* OEM Approved product
* High and very stable viscosity index
* Very good detergency and dispersion
* Fast cold start

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • **www.granvilleoil.com**

Revision: 2 | Date: 07/07/2017

Granville®

TECHNICAL DATA

Veedol
Powertron Plus 5W/40

1 Litre & 5 Litre

PRODUCT USAGE

Recommended for applications where this grade and specification of lubricant is required

DIRECTIONS FOR USE

Use as per the engine manufacturers handbook

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	:	Amber oily liquid
Odour	:	Characteristic
Specific Gravity	:	0.858 @ 15 °C
Solubility	:	Insoluble in water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • **www.granvilleoil.com**